



Dante 4 in 4 out Transmitter



Dante 4

Features:

- Dante 4x4 input/output interface can add 4 channels (input and output) for the existing network audio system at low cost
- Compact design enables being installed near an analog signal source or receiver easily
- High index DC power is adopted to the built-in electric microphone


Dante 8-in 8-out Transmitter



Dante 448

Features:

- Built-in DSP enables signal routing, EQ, limiting, noise gating and programming
- Integrated with Dante audio network port
- 4 Analog input and output;
- 4 Digital input and output for Dante network
- Support software control and programming through RS-232 port
- Built-in 8x8 matrix enables seamless mixing and routing for Analog and Digital signals.



Professional Sound Card

DSC-200

Features:

- Adopt high-class DSP chip of high sampling rate and with one stereo and two XLR outputs
- Compact design and convenient to carry
- Built-in headphone output for monitoring and playback
- Quick installation and operation, no need for driver program.



TECHNIQUE INDEX

SPECIFICATIONS	DSC-200
Output	1* 1/4" Stereo; 2 * XLR
Max. Output Level	0dBu
Frequency Response	20~20KHz
Sampling Rate	32/44.1/48KHz
Connection	USB 2.0
Operation System	Windows XP or higher
Power Consumption	2.5W
Gross Weight	1.1 Kg.
Dimensions	81(H) x 52(W) x 121(D) mm

Dante Panel 2 Dante Wall Panel 2*2



Description:

Dante Panel series wall-mounted interface machines boast analog input and Dante digital input, analog line output and Dante digital output. The analog inputs support phantom power and manual preamp-gain adjustment. It is suitable for room and other professional applications. It available in black and white color.

TECHNIQUE INDEX

Model	Dante 448
Input	8 balanced/unbalanced input (XLR)
Input Impedance	Greater than 2000 Ω
Max. Input Level	+4dbu@ 0dB gain
Output	8 balanced/unbalanced output (XLR)
Output Impedance	400Ω
Max. Output Level	+4dbu balance
Freq. Response	20~20KHz, ±1dB
S/N Ratio	Greater than 55dB
THD	Less than 0.05%
Power Requirements	12V DC
Dimensions	44(H) x 178(W) x 22(D) mm

Model

Sampling	48k@24bit
Phantom power	DC 48V
Frequency response	20Hz~20KHz, ±0.7
THD+N	50.005%@1k, ±0.7
Digital-to-analog/analog-to-digital	105dB
dynamic range(A-weighted)	
Input/output impedance(balance-type)	20k Ω / 100 Ω
EIN(A-weighted)	S-126dBu
Channel isolation	100dB@1kHz
Common mode rejection (CMR)	80dB@80Hz
Max. input/output level	8dBu/12dBu
Background noise	-93dBu
System delay	53ms
Operating power supply	PoE
Operating temperature	0~40°C