



# Compact PA System



Series

## Slim Active Speaker System



### Features

- The full-range column speaker is housed in an elegant and sturdy aluminum alloy chassis. The subwoofer cabinet is made of high-quality plywood coating with anti-scratch paint.
- The high power SMPS amplifier housed on the subwoofer is a 4-channel Class D amp with DSP processing. This ensures clean and smooth mid highs but emphatic and rich lows.
- Multiple signal input options, flexible applications.
- Built-in Bluetooth receiver realizes control and listening to your favorite music wirelessly.
- The newly developed, integrated mounting pole enables far more convenient connection and selection of sound coverage angle.
- More stylish design and all functions integrate into one system, fast set-up and effortless handling.
- Built-in multiple DSP preset optional.
- Built-in professional effect processor, multiple effects optional.

### Description:

KQ-33 is a plug and play active speaker set best for small live shows, small parties, bands, musicians and any sound reinforcement system which portable is the essential issue. The full range column speaker is coming with sturdy aluminum alloy housing. Excellent impact resisting performance, elegant finishing with glossy PU paint against scratch and smart structure in a very compact package make the speaker ideal for a great variety of applications. The subwoofer is equipped with high damping factor 12" woofer, delivering emphatic and rich lows. Presided port designs not only help the speaker to keep clear and good sound but also lower noise and minimize distortion. Column speaker perfectly matches to powered subwoofer, giving stunning sound reproduction in almost any application or different kinds of venues. KQ-33 is surely the most popular extra compact high power active speaker system worldwide. It features versatility, easy operation, extremely portable and wide application.

### Specifications:

Model	KQ-33 TOP	KQ-33 SUB
Frequency response	100Hz-18KHz	40Hz-250Hz
Directivity	H120°xV15	—
Impedance	6 ohm	8 ohm
Rated power	200W	300W
Peak power	800W	1200W
Sensitivity	95dB	99dB
Max SPL	124dB	131dB
Protection	—	Opto-limiter, Subsonic filter
Power supply	—	100-240 V AC, 50-60Hz, 15-0.6A
Power connector	—	IEC
Product dimensions	977x318x168mm	642x418x592mm
Net weight	9.0kg	27.0kg