

Colinear Active Speaker System



- Features**
- Italian high-end drivers.
 - King Kong sand paint finishing for anti-scratches and anti-collision.
 - Built-in dual channel class-D amplifier with DSP control ensures big dynamic but extra compact system.
 - Colinear source design.
 - Fast rigging hardware.
 - Designed according to the golden ratio of ear hearing.
 - Equipped multiple rigging points, wall mounting and flying are possible.

Specifications:

Model	KQ-5 TOP	KQ-5 SUB
Frequency response	90Hz-19KHz	45Hz-280Hz
Drivers	H1: 2x1"compress1on driver Low:6x5"(25mm voice coil)	2x13 5"(80mm voice coil)
Directivity angle	H100° xv10	—
Sensitivity	98dB	103dB
Impedance	6ohm	4ohm
Long-term power(RMS)	400W	700W
Power peak	800W	1400W
Maximum SPL	127dB	134dB
Power supply	—	AC 110v-240V750Hz
Output power	—	500W+1000W
PC interface	—	One USB interface on front panel DSP
Connector	1x4-pin Speakon	2XLR+1x4-pin Speakon+1 Powercon
Product/shipping dimension(WxDxH)	1 x4-pin Speakon1160x198x150/ 1210x390x430mm	386x545x700/1210x390x430mm
N.W/G.W	16.0kg/ 46 0kg(x2)	42.0kg/102.0kg(x2)

Description:

KQ-5 TOP and KQ-5 SUB are a colinear sound system which is precise configured to achieve constant coverage at wide frequency range. KQ-5 SUB features vented bass enclosure with two 13.5 inch long-throw woofers, providing low frequency contour and extended bandwidth to KQ-5 TOP, delivering heavy low but also rich mid, tailed for KQ-5 speaker as a stunning sound system. It can easy and fast ground stack setting up with KQ-5 SUB. KQ-5 TOP can be stacked as a standalone system or secured onto one of its LF extensions. It is a versatile sound system for different kinds of applications. It is also a good system for portable sound or live sound.