

18" compact high power subwoofer



PSTX818S

Single 18" Bass Reflex Subwoofer


A single 18" compact high power subwoofer system in a front-loaded, vented enclosure designed for minimum distortion provides 1,000 watts of continuous pink noise power handling, 2 kW program and 4 kW peak. The PSTX818S also comes equipped with a top-mounted M20 pole-mount and an optional wheel kit.

Application:

- 18 in. Super Vented Gap™ woofer for extended low-frequency output.
- Large port area for reduced distortion.
- 20 mm threaded pole socket for solid, secure satellite speaker mounting.
- Rugged DuraFlex™ coated enclosures sized to be truck pack friendly.
- 14-Gauge steel grille lined with acoustically transparent cloth.

TECHNIQUE INDEX


Model	PSTX818S	PSTX818S+
Operational Modes	Subwoofer	Subwoofer
Frequency Range (-10 dB)	35 Hz-250 Hz	35 Hz-250 Hz
Frequency Response (± 3 dB)	40 Hz-120 Hz	40 Hz-120 Hz
Sensitivity (1W/1m)	96 dB	96 dB
Nominal Impedance	8Ω	8Ω
Rated/Continuous/Peak power	800W/1600W/3200W	1000W/2000W/4000W
Maximum SPL	125dB/128dB/131dB	125dB/128dB/132dB
Input Connectors	Two NL4	Two NL4
Dimensions (H x W x D)	558 mm x 568 mm x 718 mm (22.0" x 22.4" x 28.3")	558 mm x 568 mm x 718 mm (22.0" x 22.4" x 28.3")
Net Weight	45 kg (100 lbs)	45 kg (100 lbs)



dual 15" two-way speaker



PSTX825



Dual 15" Two-Way, Bass-Reflex

PSTX825 is a dual 15" two-way speaker designed for maximum impact, portability and ease of use. With a wide frequency range and broad 90 degree by 50 degree coverage angles, this speaker is ideal for bands or DJ's as their primary PA, used as a side-fill on a concert stage, or as an install speaker in a dance club or performance venue.

Application:

- Compact and very high-power.
- Dual (15") Vented Gap Cooling™ low-frequency drivers for very high acoustic output.
- 102 mm (4 inch) voice-coil neodymium compression driver for high-power capacity and very light-weight
- 90° x 50° coverage
- 8Ω-impedified or full-range passive operation.
- Tweeter M10 suspension points may be used with optional M10 eyebolts.
- Rugged DuraFlex™ coated enclosures sized to be truck pack friendly.
- 14-Gauge steel grille lined with acoustically transparent cloth.

TECHNIQUE INDEX

Model	PSTX825
Configuration	100 core .440 magnetic LF-86 core HF
Frequency Range (-10 dB)	34 Hz-20 kHz
Frequency Response (± 3 dB)	42 Hz-19 kHz
Sensitivity (1W/1m)	98 dB
Nominal Impedance	4Ω
Rated/Continuous/Peak power	1000W/2000W/4000W
Maximum SPL	128dB/131dB/134dB
Coverage Pattern	90° x 50° nominal
Input Connectors	Two NL4
Operational Modes	Full Range/Bi-Amp
Net Weight	51 kg (112 lbs)
Dimensions (H x W x D)	1086 mm x 568 mm x 573 mm (42.0" x 22.4" x 22.6")