

12" two-way stage monitor



PSRX712M


12" High-Power Two-Way Stage Monitor

The PSRX712M was designed with one goal-build the lightest, smallest, loudest, clearest stage monitor possible while delivering strikingly professional appearance.

- Application:**
- Compact and low-profile for minimal obstruction of audience sight-lines.
 - 90° x 50° nominal coverage.
 - Bi-amplified or full-range passive operation.
 - Dual-angle pole socket for applications requiring tripod mounting.
 - Optional yoke available for trussmounted or suspended applications.
 - Neodymium magnet Differential Drive® woofer for high-power capacity and very light-weight.
 - 3-inch (diaphragm) neodymium magnet compression driver.

TECHNIQUE INDEX

Model	PSRX712M
Configuration	190 magnetic LF, 44 core HF
Frequency Range	70 Hz - 20kHz (-10 dB)
Frequency Response	83 Hz - 18 kHz (+3 dB)
Sensitivity (1m/1W)	96dB
Rated/Continuous/Peak power	400W/800W/1600W
Maximum SPL	122dB/125dB/128dB
Coverage Pattern	90° x 50° nominal
Net Weight	15 kg (33 lb)
Dimensions (H x W x D)	349 mm x 546 mm x 260 mm (13.75 in x 21.5 in x 10.25 in)



15" two-way



PSRX715

15" High-Power Two-Way Loudspeaker

The PSRX715 offers the highest level of performance available from a portable, pole or tripod mountable speaker.

- Application:**
- Lightweight and very high-power.
 - 75° x 50° coverage.
 - Bi-amplified or full-range passive operation.
 - Dual-angle pole socket for applications requiring tripod mounting.
 - Flying version available (PSRX715F) with five suspension points. May be used with optional M10 eyebolts or detachable track fittings.
 - Differential Drive® woofer with magnet for high power capacity and very light-weight.
 - 3-inch (voice-coil) compression driver

TECHNIQUE INDEX

Model	PSRX715
Configuration	100 core 220 magnetic LF, 75 core HF
Frequency Range	40 Hz - 20kHz (-10 dB)
Frequency Response	53 Hz - 20 kHz (+3 dB)
Sensitivity (1m/1W)	97dB
Rated/Continuous/Peak power	500W/1000W/2000W
Maximum SPL	124dB/127dB/130dB
Coverage Pattern	75° x 50° nominal
Net Weight	22 kg (48 lb)
Dimensions (H x W x D)	711 mm x 439 mm x 406 mm (28 in x 17.3 in x 16 in)

