

Long Throw 18 inch full range speaker covering 1 KM

Features:

Portable sound system with wheel case
 The PA Portable sound system is a versatile, high-performance, full-range speaker & subwoofer system for mobile sound reinforcement needs.
 Passive Built-in 2 way design with 2 Neutrik NL4 plug, Neodymium magnet/ Ferrite magnet drivers optional, birch 18mm cabinet, anti-scratch textured paint coating, integrated in four wheels case to enable easy transportation, make it professional and widely used in occasions like touring show, shopping mall, hall ,meeting room ,small stage etc. Definitely a good choice for touring sound reinforcement needs.



PA928

TECHNIQUE INDEX

Model	PA928
Units	2x18"±220 mm ferrite magnet,Al basket
Frequency Response	±3dB, 45-19KHZ
Sensitivity(1m/1W)	102 dB
Rated/Continuous/Peak power	1100W/2200W/4400W
Maximum SPL	132dB/135dB/138dB
H X V	/
Impedance	4Ω
Connector	NL4x2,+1/-1
Size	1160x925x580mm
Weight	105KG

Outdoor long-throw Point source speaker

Features:

- Point source sound wave direction
- Dual 12 inch Dual 15 inch design, mass output
- Magnet, ferrite / Neodymium driver
- Outdoor, Open air activities / gathering sound reinforcement solution.



RX212



RX215

TECHNIQUE INDEX

Model	RX212
Units	LF: 2X12" 75mm voice core, Neodymium driver HF: 1X1.75" Neodymium driver"
Frequency Response	60-18K Hz
Sensitivity(1m/1W)	96dB
Rated/Continuous/Peak power	900W/1800W/3600W
Maximum SPL	126dB/129dB/132dB
H X V	90°x60°
Impedance	8Ω
Connector	NL4x2,+1/-1
Size	460x451x732mm
Weight	21KG

Model	RX215
Units	LF: 2X15" 75mm voice core, Neodymium driver HF: 1X3" 1 ferrite driver"
Frequency Response	55-18.5K Hz
Sensitivity(1m/1W)	100dB
Rated/Continuous/Peak power	1000W/2000W/4000W
Maximum SPL	130dB/133dB/136dB
H X V	100°x60°
Impedance	8Ω
Connector	NL4x2,+1/-1
Size	500x534x893mm
Weight	36KG