

LAS-210 + LAS-215 SUB line array system



LAS-210 is a double 10" full range line array speaker. It features high power but extra compact cabinet, low distortion but high SPL, flexible combination but light weight, making it the best choice for many kinds of applications no matter touring, rental or permanent installations. Benefits from our decades of manufacturing self-powered systems, including carrying internal amplification, complex crossover, driver protection and frequency and phase correction circuitry on board. All components were all special designed to meet stringent performance requirements. Each speaker contains all of its amplification and processing within the loudspeaker cabinet, providing greater performance, lower cost and more convenience. Quick-ry rigging hardware is fixed on the cabinet. Flying the speakers as the array is a snap.

CHARACTERISTIC

- Our proprietary aluminum rigging hardware for easy and fast setting up.
- Multiple angles option for precise dispersion.
- Highly noise absorbable materials.
- Flexible application and easy installation.
- Patent made neodymium drivers.
- Better for transportation protection (Specs each flight case).
- Environmental Kmg Kong painting finishing.
- Super harden steel grille.
- Multi-layer birch laminate construction.
- Best for touring sound, indoor or outdoor medium-size sound reinforcement or permanent installation for multi function halls, stadiums and the like.

LAS-210 → Both passive and active versions are available.

TECHNIQUE INDEX

Model	LAS-210
Drivers	Ht:1x2.5" neodymium driver (2.5 voice coil), Low:2x10" neodymium woofer (2.5 voice coil)
Frequency response	50Hz-18KHz
Directivity angle	H100°xV10°
Sensitivity	Low:106dB Ht:106dB
Impedance	Low:8 ohm Ht:8 ohm
Long-term power(RMS)	Low:600W Ht:100W
Continuous	Low:1200W Ht:200W
Power peak	Low:2400W Ht:400W
Maximum SPL	Low:126dB Ht:126dB Pnk:Low:137dB Ht:127dB
Connection	2x4-pin Speaker (1+1 LOW /2+2 HI)
Shipping dimensions(WxDxH)	905x450x319mm(35.6x17.7x12.5)
N.W./G.W	18.0kg/22.2kg(42)

LAS-215 SUB line array speaker



LAS-215 SUB is dual 15" subwoofer tailored for either touring or permanent installation. The speaker is Vented Band-Pass construction to achieve most compact cabinet, minimum distortion, optimal amplitude and smooth phase response. The cabinet is coated by abrasive wear resistant material finishing. Two 15" neo woofers with 3" voice coil produce super strong bass, which can easily satisfy all your demands at a sound system.

CHARACTERISTIC

- Vented Band-Pass construction.
- 15" neodymium woofers with 3" voice coil.
- High density sound absorbable materials.
- Proprietary suspension hardware.
- Italian-made neodymium woofers.
- Imported super hard amebatch finish.
- Eco-friendly and fast transient response.
- Multi-layer plywood.
- Best for bands, music halls, churches, multi-function halls and likewise.

Both passive and active versions are available.

LAS-215 SUB.

LAS-215 SUB DRAWINGS

