

Column speaker

E series column speaker system



Features:

- 1x 6.25" ferrite LF driver, 45mm voice coil.
- 1x 1.3" dia. 80 mm ferrite magnet HF driver, 34mm Polyester diaphragm with Hydra horn, 90° x45° waveguide
- 15mm birch plywood ,anti-scratch Polyurea coatings
- With bolts in the cabinet for rigging or installing
- suitable for auditorium, church, multi-function hall, mobile performance applications etc
- Standard Acquired: GBT 12060.5-2011 IEC 60268-5, 2007 GBT 9397-2013

Optional Accessory:



M20 post
For connecting E618 and E601
as a system



Specifications:

Model	E601
Color	Black
Plugs	2x Neutrik® NL4
Fre Response(-3dB)	70-20kHz
Sensitivity(1w/1m)	95dB
Rated Power(RMS/ Peak 10ms)	200/400W
Max SPL	121dB
HxV(-6dB standard)	75° x 45°
LF driver	1 x6.25-in
HF driver	1 x1.3-in
Impedance	8Ω
Size(WxHxD)mm	228x113x358x250
Weight(kg)	8.5

E series column speaker system



Features:

- 2x 6.25" ferrite LF driver, 35mm voice coil.
- 1x 1.75" HF driver, Neodymium dia 102 mm magnet, 44mm Polyester diaphragm, with Hydra horn, 90° x45° waveguide.
- 15mm birch plywood, anti-scratch Polyurea coatings
- With bolts in the cabinet for rigging or installing
- Suitable for auditorium, church, multi-function hall, mobile performance applications etc
- Standard Acquired: GBT 12060.5-2011 IEC 60268-5, 2007 GBT 9397-2013

Optional Accessory:



M20 post
For connecting E618 and E602 as a system



Specifications:

Model	E602
Color	Black
Plugs	2x Neutrik® NL4
Fre Response(-3dB)	70-20kHz
Sensitivity(1w/1m)	98dB
Rated Power(RMS/ pEAK 10ms)	350/700W
Max SPL	126dB
H x V(-6dB)	75° x45°
LF driver	2 x6.25-in Ferrite
HF driver	1 x1.75-in Neodymium
Impedance	16Ω
Size (WxHxD)mm	228x113x532x250
Weight (kg)	13