

**KING Professional mixer console**




**KING-416 / KING-424 / KING-432**

**CHARACTERISTIC**

- 32-way max. inputs, 4-way stereo, +48V phantom power supply, independent switch control, High-pass filter selector switch
- Pre-amplifier with high stability and low noise provide the operator with suitable level dB output
- On each way has, high pass filter, insertion points (INSERT), 4 band frequency scan equalizer with switch selection, 4 band LED pass level indicator, direct output (DIRECT)
- Mute and monitor switch are installed on channels of incoming and output signals. Powerful SOLO tracking system for freely monitoring of mixing output, including outputs of stereo, mono, auxiliary, group and record, Headphone monitor bus can be selected for stereo or mono.
- The intercom system can be transmitted to any output group
- Output channels include 2 mixing stereos (Master L and Master R), 2 auxiliary mixer stereos, Master B (can be switched to 2 stereo mixing and sum outputs), 4 group outputs, 4 monitor outputs, and 4 auxiliary outputs. There are 14 band LEDs for each output
- Outside power supply to reduce background noise

**KING Professional mixer console**



**TECHNIQUE INDEX**

product model	KING-416	KING-424	KING-432
Input	8 MIC+4 stereo	16 MIC+4 stereo	24 MIC+4 stereo
Aux output/return	4/8	4/8	4/8
Output group	4+2(A) +2 (B)	4+2(A) +2 (B)	4+2(A) +2 (B)
Parameter equalizer	4 band 2 band scan	4 band 2 band scan	4 band 2 band scan
Frequency response	20Hz-20KHz	20Hz-20KHz	20Hz-20KHz
SNR	> 100dB	> 100dB	> 100dB
Total harmonic distortion	< 0.05%	< 0.05%	< 0.05%
LINE/MIC Input impedance	10KΩ/1.6KΩ	10KΩ/1.6KΩ	10KΩ/1.6KΩ
Output Impedance	75Ω	75Ω	75Ω
Input channel port	XLR/TRS	XLR/TRS	XLR/TRS
Output channel port	XLR/TRS	XLR/TRS	XLR/TRS
power supply	220V/240V AC50-60Hz/75W	220V/240V AC50-60Hz 95W	220V/240V AC50-60Hz 120W
size(L×W×H)(mm)	510×568×194/60	720×568×194/60	930×568×194/60
Net weight	16.4kg	22kg	25.8kg



**Back**