



F Series Mixers with USB, Mp3, & BT



F4-MB



F4-MB / F7-MB

Features:

- LR main mix
- Quick response, beautiful 3-band channel equalizer
- Channel peak and main level indicator
- 2 channels per channel to send
- 60mm dust fader
- 2 track monitor and replay to LR
- Ultra low noise mixing design
- MP3 player, supports a variety of audio formats,
- Bluetooth and recording
- Metal rack, gold plated XLR (XLR) plug, sealed potentiometer and switch
- External power adapter powered

TECHNIQUE INDEX

Maximum input level microphone	+24dBu
Line	+24dB
The maximum output level	+26 dBu
Main level meter	5 segment LED
Frequency response	20Hz to 20KHz ± 0.5dB
Common mode rejection ratio (CMR) (KHz)	> 75 dB
Common mode rejection ratio (CMR) (KHz)	> 75 dB
Crosstalk (1K Hz)	< -65 dB
Crosstalk (1K Hz)	< -65 dB
Noise (20Hz to 22K Hz)	Equivalent input noise < -116dBu
Remaining output noise	< -80 dBu
Mono / Stereo Channel EQ	High Frequency, Broth, ± 15dB, 12K Hz
High Frequency, peak and valley type, ± 15dB, 2.5K Hz	
Low Frequency, broom type, ± 15dB, 80Hz	
Mono XLR balanced, 2-pin hot end, -2K ohm, sensitivity -60 to +14 dBu	
TRS Phantom Power +48V	
XLR balanced, tip hot 10Kohm, sensitivity -40 to +14 dBu	
STEREO TRS balanced, tip hot 10Kohm, sensitivity -40 to +14 dBu	
STEREO TRS balanced, tip hot 10Kohm, sensitivity -40 to +14 dBu	
FX/AUX output TRS unbalanced, tip hot end, -27.5 ohm, max +18dBu	
FX/AUX output TRS unbalanced, tip hot side, < 75 ohm, max +18dBu	
Headphones TRS tip, L, ring R, recommended 30 to 600 ohm headphones	
Maximum power input power	4/7 channel   15 W
Dimensions	4channel   7 channel
Width	210mm   330mm
Depth	230mm   230mm
Height	37mm   37mm

F7-MB



Powered Audio Mixer

Features:

- 6/8/10/14 channels mixer with plastic case
- with 99/dual 99 DSP effect
- with MP3, USB, Bluetooth
- with +48V phantom power
- with 5 band/7 band/9 band/dual 9 band main EQ



PMX-6 C500



PMX-6 C500 MIC



PMX-8 C700  
PMX-8 C1200



PMX-10 C700  
PMX-10 C1200



PMX-14 C700  
PMX-14 C1200

TECHNIQUE INDEX

Model	PMX-6 C500	PMX-6 C500 MIC	PMX-8 C700	PMX-8 C1200	PMX-10 C700	PMX-10 C1200	PMX-14 C700	PMX-14 C1200
Line channel	6 mono	6 mono	8 mono	8 mono	6mono+2Stereo	6mono+2Stereo	6mono+4Stereo	6mono+4Stereo
EFFECT	99 DSP	99 DSP	99 DSP	99 DSP	dual 99 DSP	dual 99 DSP	99 DSP	99 DSP
Main EQ	5 Band	5 Band	7 Band	7 Band	7 Band	7 Band	Dual 9 band	Dual 9 band
Phantom Power	48V DC	48V DC	48V DC	48V DC	48V DC	48V DC	48V DC	48V DC
Power amplifier output max power	250W X 2 (8Ω)	250W X 2 (8Ω)	350W X 2 (8Ω)	600W X 2 (8Ω)	600W X 2 (8Ω)	600W X 2 (8Ω)	350W X 2 (8Ω)	600W X 2 (8Ω)
Other function	MP3, USB Bluetooth	MP3, USB, Bluetooth, 2 wireless mics					with MP3, USB, Bluetooth	
Case Material	Plastic	Plastic	Plastic	Plastic	Plastic	Plastic	Plastic	Plastic