

FEATURES

TX318S

- **High-quality sound:** A professional 18-inch waterproof subwoofer delivers clear and powerful bass that enhances the overall audio experience. The subwoofer handles high power and produce a deep, rich sound.
- **Waterproof design:** The subwoofer is designed to withstand exposure to water and other elements. This is especially important for outdoor installations or in areas where moisture is present.
- **Durable construction:** The subwoofer is built to last, with a rugged construction that can withstand heavy use and abuse. It is made from high-quality materials and have a robust design that minimizes the risk of damage or failure.
- **Easy installation:** The subwoofer is easy to install, with clear instructions and all the necessary hardware included.
- **Versatile use:** A professional 18-inch waterproof subwoofer is suitable for a wide range of applications. It is versatile and flexible enough to meet the needs of different users and environments.

18" Outdoor Waterproof Subwoofer



TX328S

- **Powerful Bass:** A dual 18" outdoor waterproof subwoofer is designed to deliver powerful bass that can enhance the overall sound quality of any outdoor sound system. With its large drivers and high-power handling capacity, this subwoofer can produce deep, rich bass tones that can be felt as well as heard.
- **Weather-resistant:** The subwoofer is built to withstand harsh outdoor conditions such as rain, snow, and extreme temperatures. It is constructed with weather-resistant materials that can protect it from moisture and other environmental factors, ensuring long-lasting durability.
- **High sensitivity:** The subwoofer has a high sensitivity rating, which means it can produce loud and clear sound with minimal power input. This makes it ideal for large outdoor areas where a powerful sound system is necessary.

TECHNIQUE INDEX

Model	TX318S	TX328S
AES Power	600W	1200W
Power Peak	2400W	4800W
Frequency Response	30Hz-300Hz	40Hz-300Hz
Driver	18" LF driver	18"x2(460mm)/4"(100mm) voice coil LF driver
Impedance	8ohm	4ohm
Sensitivity	98dB	99dB
Maximum SPL	132dB	136dB
Connector	2xNL4R speakon	2xNL4R speakon
Product Dimensions	560x600x780mm	1066x780x561mm
Shipping Dimensions	622x662x842mm	1195x920x720mm
N.W/G.W	47kg/52kg	80kg/87kg